

Perforated Metal Plank Type BN-GA

The surface of the perforated metal plank, type BN-GA 'Noppen, geschlossen, Ablauflöcher' is a mix of closed punched nobles facing upwards and conical drain holes facing downwards. This means that the grating does not have any sharp edges on top and can be walked on easily even without footwear. At the same time, however, any liquids can be quickly drained through the conical drain holes so that no hydroplaning can occur.

Technical Details

Material	Steel S235JR:	2,0 mm, 2,5 mm
	Stainless Steel:	2 mm,
	Aluminium:	2 mm, 2,5 mm
Surface treatment	Steel:	untreated, hot-dip galvanized, pre-galvanized
	Stainless Steel:	untreated, pickled
	Aluminium:	untreated, pickled, anodized
Free cross section	Max. ~ 2,4 %	
Width	150 mm, 200 mm, 250 mm, 300 mm (other widths possible in demand)	
Height	30 mm, 50 mm, 75 mm, 100mm, 150 mm (Corresponding to width and statical specification)	
Ball proof	100% full filled, closed surface	
Slip resistance	R10 / V10 (Steel hot-dip galvanized IFA1404164)	
Longitudinal grid	125 mm (62,5 mm)	
Production length	max. 10 m, depending transport limited	

