

PRODUCT INFORMATION

CADAOIL GEARBOX CVT

Full synthetic automatic transmission fluid for CVT's

Cadaoil Gearbox CVT is a full synthetic transmission oil for the lubrication of modern Continue Variable Transmissions (CVT's).

Cadaoil Gearbox CVT can be applied in all metal-belt, which are mentioned under Performance Level.

Cadaoil Gearbox CVT offers optimal protection of the CVT under every condition and prevents wear at the metal contact points on the belts and pulleys.

Cadaoil Gearbox CVT protects the metal parts against wear and corrosion as well as inconvenient vibrations. Because of the special additives this oil has a durable quality, even under ongoing pressure.

Cadaoil Gearbox CVT is formulated to prevent air entry and foam building in order to guarantee optimum lubrications.

PERFORMANCE

BMW 83 22 0 136 376 CVT EZL 799 A Daihatsu CVTF DFE Dia Queen CVTF J1 EZL-799 Mopar CVTF +4 Nissan NS-1 Suzuki CVTF Green 2 Toyota CVT TC Ford WSS-M2C928-A BMW 83 22 0 429 154
DAIHATSU AMIX CVT FLUID
Daihatsu/Suzuki TC Dia
Queen CVTF J4
Ford CVT23
Nissan NS-3
Subaru Lineartronic CVTF
Suzuki NS-2
VW G 052 180

DC
DEX-CVT
Elf Matic CVT
MB 236.20
Nissan NS-2
Suzuki CVT Green 1
Toyota CVT FE
VW G 052 516

Chrysler CVTF+4

| Colour | Amber | |
|-------------------------------|-------------|-------------|
| Density at 20°C | 0.8493 kg/l | ASTM D 1298 |
| Viscosity, kinematic at 40°C | 33.6 cSt | ASTM D 445 |
| Viscosity, kinematic at 100°C | 7.2 cSt | ASTM D 445 |
| Viscosity Index | 186 | ASTM D 2270 |
| Flash point | 130 °C | ASTM D 93 |
| Pour point | -42 °C | ASTM D 97 |

This sheet contains recommendations or suggestions on properties and possible applications of Cadaoil products. Because of continuous product research and development, the information in this document can be changed at all times, without foregoing notice. The analytical information in this document consists of typical incorrectness of the text. The reader is advised to make the final product choice in dialogue with the supplier.