



## PFA

### LABEL MATERIAL

- Self-adhesive label material for direct marking in cabinets and on components.
- Label modules pre-punched in standardized 17.5 mm units.
- Easy to separate polyester foil on paper base, specially preprocessed for printing.
- Halogen free.
- Very durable and environment resistant printout by laser printer.
- Fast, smart and easy marking on-site with Partex software WinSign.

### GENERAL INFORMATION

#### Design

Perforated self-adhesive display material with adhesive on paper base. Folded sheets A4 width and tractor feed. 12" sheet length with tear initiation.

The PFA label is intended for component marking with the standardized mule width of 17,5 mm.

#### Material

Self-adhesive polyester foil, specially pre-processed for printing.

#### Colours

White or yellow. Other colours, please contact Partex.

#### Print / Text

Printed with aid of Partex software WinSign and by Partex recommended laser printer.

WinSign handles the Windows installed True Type fonts.

#### Temperature range

From -30°C to +120°C (-22°F to +248°F).  
 NB! Withstands laser printing.

#### Resistance

Withstands most solvents.

Note: Store in a cool place, away from sunlight. Maximum storage time up to two years to maintain good adhesion.

For application in hostile environments, please contact Partex for information.

Article number	Label height	Label length	Number of labels (row x columns)	Number of 12" sheets/packs	Total number of labels/packs
PFA20018KT*	9.5 mm	17.5 mm	10 ark X 32 X 11 pcs	10 pcs	3520 pcs