PURION Pool 40



The integrated plant PURION PooL 40 consists of a filtration of sediments and UV based disinfection of pool water. It is applied to disinfect circulation water of pools.

The pre filter removes sediment from the pool water. The following UV based disinfection prevents biological activities especially forming of algae.

product line	PURION Pool 40
pool dimension	$40m^3$ (20 h operation) $30m^3$ (15 h operation)
dimension (L x B x H in mm)	770 x 530 x 940
UV plant	PURION 2001
life time of lamps	10.000 h
max. delivery rate rotary pump	6 m³/h
weight (without quartz granulate)	34 kg
quantity quarztz	35 kg
valve filter tank	top mount 4 port valve
protection grade	IP 54
electrical connection	230 V
over current protection	10 A
	pool dimension dimension (L x B x H in mm) UV plant life time of lamps max. delivery rate rotary pump weight (without quartz granulate) quantity quarztz valve filter tank protection grade electrical connection

1st step: filtration of sediments

The upstream filter unit with "top mount" 4-port valve consists of a polyethylene filter tank (filled with activated filter granulate - special quartz) and a rotary pump. This pre filter has two layers with different granulate

dimension that removes sediment from the pool water.

2nd step: disinfection with UV-light

The following UV based disinfection prevents biological activities - especially the formation of algae.

Unlike other cleaning procedures this approach does not produce potentially dangerous byproducts.



article-no.: 140 00100 0000 article-no.: 140 00200 0000

equipment PURION Pool 40

Quartz-granulate fine granularity article number: 292 02300 0000

Quartz-granulate coarse granularity article number: 292 02400 0000



stainless steel PVC-U

.

service-kit article number: 292 00900 0000

article number: 200 00500 0000

PURION UV-lamp 48 W

PURION

