

IBC TANKS

PM10, PM11, PM12 IBC tanks are commonly used for storage and transportation of chemicals, fluids, food and dangerous materials usually required by UN certification of storage.

CAPACITY – effective 1000L capacity, effective for transportation.

USAGE – simple and fast fill in, with 2 inch and 3 inch valve, wide inlet (150mm and 225mm).

SAFETY – Made of high density and quality PE. Resistant to acids, alkalines, oils and other chemicals.

Provided with metal housing and pallet – PM10 wood, PM11 plastic, PM12 plastic.



PM10 with wooden palette

Dimensions:

Height:	1170 mm ± 5 mm
Base:	1200 mm x 1000 mm ± 5 mm
Total weight:	60,5 kg

Tank:

Material:	HDPE
Total capacity:	1085 l
Colour:	Natural
Optional colour:	Black and white
Przyłącze zaworu:	Standard DN50 butterfly valve
Optional:	Butterfly vavle DN 50 with camlock
Optional:	Camlock valve DN50
	Ballvalve

Cover:

150 mm standard:	Black, Optional: per customer request
225 mm standard:	Black, Optional: per customer request
Standard gasket:	EPDM
Optional gasket:	Viton®
Optional degassing gasket:	Gore®

Valve:

Butterfly valve 2":	DN50
Gasket:	ETFE
Return ring gasket:	Elastomer, Viton
Connector:	s60x6
Chocke valve 3":	DN80
Connector:	s80x8
Gasket:	ETFE
Return ring gasket:	standard Viton®

Palette mark:

Small	400mm x 240mm
Medium	425mm x 545mm
Large	425mm x 700mm

Palette:

Wooden palette:	1200mm x 1000mm x 135mm
Optional:	15 ISPM heat treatment

Metal housing:

Pipes specification:	0.9mm thickness, round profile
----------------------	--------------------------------



PM10 UN with wooden palette

Dimensions:

Height:	1170 mm ± 5 mm
Base:	1200 mm x 1000 mm ± 5 mm
Total weight:	60,5 kg

Tank:

Material:	HDPE
Total capacity:	1085 l
Colour:	Natural
Optional colour:	Black and white
Przyłącze zaworu:	Standard DN50 butterfly valve
Optional:	Butterfly valve DN 50 with camlock
Optional:	Camlock valve DN50
	Ballvalve

Cover:

150 mm standard:	Black, Optional: per customer request
225 mm standard:	Black, Optional: per customer request
Standard gasket:	EPDM
Optional gasket:	Viton®
Optional degassing gasket:	Gore®

Valve:

Butterfly valve 2":	DN50
Gasket:	ETFE
Return ring gasket:	Elastomer, Viton
Connector:	s60x6
Chocke valve 3":	DN80
Connector:	s80x8
Gasket:	ETFE
Return ring gasket:	standard Viton®

Palette mark:

Small	400mm x 240mm
Medium	425mm x 545mm
Large	425mm x 700mm

Palette:

Wooden palette:	1200mm x 1000mm x 135mm
Optional:	15 ISPM heat treatment

Metal housing:

Pipes specification:	0.9mm thickness, round profile
----------------------	--------------------------------



PM11 with plastic-metal palette

Dimensions:

Height:	1151 mm ± 5 mm
Base:	1200 mm x 1000 mm ± 5 mm
Total weight:	52,5 kg

Tank:

Material:	HDPE
Total capacity:	1085 l
Colour:	Natural
Optional colour:	Black and white
Przyłącze zaworu:	Standard DN50 butterfly valve
Optional:	Butterfly valve DN 50 with camlock
Optional:	Camlock valve DN50
	Ballvalve

Cover:

150 mm standard:	Black, Optional: per customer request
225 mm standard:	Black, Optional: per customer request
Standard gasket:	EPDM
Optional gasket:	Viton®
Optional degassing gasket:	Gore®

Valve:

Butterfly valve 2":	DN50
Gasket:	ETFE
Return ring gasket:	Elastomer, Viton
Connector:	s60x6
Chocke valve 3":	DN80
Connector:	s80x8
Gasket:	ETFE
Return ring gasket:	standard Viton®

Palette mark:

Small	400mm x 240mm
Medium	425mm x 545mm
Large	425mm x 700mm

Palette:

Plastic-metal palette:	1200mm x 1000mm x 135mm
------------------------	-------------------------

Metal housing:

Pipes specification:	0.9mm thickness, round profile
----------------------	--------------------------------



PM11 UN with plastic-metal palette

Dimensions:

Height:	1151 mm ± 5 mm
Base:	1200 mm x 1000 mm ± 5 mm
Total weight:	52,5 kg

Tank:

Material:	HDPE
Total capacity:	1085 l
Colour:	Natural
Optional colour:	Black and white
Przyłącze zaworu:	Standard DN50 butterfly valve
Optional:	Butterfly vavle DN 50 with camlock
Optional:	Camlock valve DN50
	Ballvalve

Cover:

150 mm standard:	Black, Optional: per customer request
225 mm standard:	Black, Optional: per customer request
Standard gasket:	EPDM
Optional gasket:	Viton®
Optional degassing gasket:	Gore®

Valve:

Butterfly valve 2":	DN50
Gasket:	ETFE
Return ring gasket:	Elastomer, Viton
Connector:	s60x6
Chocke valve 3":	DN80
Connector:	s80x8
Gasket:	ETFE
Return ring gasket:	standard Viton®

Palette mark:

Small	400mm x 240mm
Medium	425mm x 545mm
Large	425mm x 700mm

Palette:

Plastic-metal palette:	1200mm x 1000mm x 135mm
------------------------	-------------------------

Metal housing:

Pipes specification:	0.9mm thickness, round profile
----------------------	--------------------------------



PM12 with plastic palette

Dimensions:

Height:	1155 mm ± 5 mm
Base:	1200 mm x 1000 mm ± 5 mm
Total weight:	56,4 kg

Tank:

Material:	HDPE
Total capacity:	1085 l
Colour:	Natural
Optional colour:	Black and white
Przylącze zaworu:	Standard DN50 butterfly valve
Optional:	Butterfly vavle DN 50 with camlock
Optional:	Camlock valve DN50
	Ballvalve

Cover:

150 mm standard:	Black, Optional: per customer request
225 mm standard:	Black, Optional: per customer request
Standard gasket:	EPDM
Optional gasket:	Viton®
Optional degassing gasket:	Gore®

Valve:

Butterfly valve 2":	DN50
Gasket:	ETFE
Return ring gasket:	Elastomer, Viton
Connector:	s60x6
Chocke valve 3":	DN80
Connector:	s80x8
Gasket:	ETFE
Return ring gasket:	standard Viton®

Palette mark:

Small	400mm x 240mm
Medium	425mm x 545mm
Large	425mm x 700mm

Palette:

Plastic palette:	1200mm x 1000mm x 135mm
------------------	-------------------------

Metal housing:

Pipes specification:	0.9mm thickness, round profile
----------------------	--------------------------------



PM12 UN with plastic palette

Dimensions:

Height:	1155 mm \pm 5 mm
Base:	1200 mm x 1000 mm \pm 5 mm
Total weight:	56,4 kg

Tank:

Material:	HDPE
Total capacity:	1085 l
Colour:	Natural
Optional colour:	Black and white
Przyłącze zaworu:	Standard DN50 butterfly valve
Optional:	Butterfly vavle DN 50 with camlock
Optional:	Camlock valve DN50
	Ballvalve

Cover:

150 mm standard:	Black, Optional: per customer request
225 mm standard:	Black, Optional: per customer request
Standard gasket:	EPDM
Optional gasket:	Viton®
Optional degassing gasket:	Gore®

Valve:

Butterfly valve 2":	DN50
Gasket:	ETFE
Return ring gasket:	Elastomer, Viton
Connector:	s60x6
Chocke valve 3":	DN80
Connector:	s80x8
Gasket:	ETFE
Return ring gasket:	standard Viton®

Palette mark:

Small	400mm x 240mm
Medium	425mm x 545mm
Large	425mm x 700mm

Palette:

Plastic palette:	1200mm x 1000mm x 135mm
------------------	-------------------------

Metal housing:

Pipes specification:	0.9mm thickness, round profile
----------------------	--------------------------------

