

KSM 125 | KSM 130

Chamfer Grinding Machine for Straight Edges

The grinding machines are suitable for precise deburring and chamfering of straight edges on hard materials. deliverable with wet-grinding unit or dust extractor.




KSM 130



KSM 125 with undercarriage and integrated extractor



Further accessories can be found in our **Accessory Catalogue**.



Applications

- **Hardened and hard materials between 40-65 HRC**

Features

- ☑ Sturdy construction with grinding wheel adjusting screw
- ☑ Water cooling provides workpiece and grinding disc
- ☑ V-Prism with micrometer chamfer adjustment
- ☑ Axial grinding wheel adjustment
- ☑ Sturdy conical 2-zone grinding disc for strong material removal

Options

- ☑ Mobile undercarriage
- ☑ Dust extraction (only for KSM 125)

Delivery contents

- ☑ Standard accessories
- ☑ Grinding disc
- ☑ Extraction socket (only for KSM 125)
- ☑ Water tub and pump (only for KSM 130)
- ☑ Operating manual

Technical data

	KSM 125 ☑	KSM 130 ☑
Motor	0.75 kW 2,890 rpm	0.75 kW 2,890 rpm
Energy	400 V, 50/60 Hz	400 V, 50/60 Hz
Vc	700 - 1,100 m/min	700 - 1,100 m/min
Maximum chamfer width	5 mm	5 mm
Grinding disk, conical	ø min. 80 mm, max. 125 mm	ø min. 80 mm, max. 125 mm
Dimensions (LxWxH)	640 x 300 x 400 mm	700 x 650 x 400 mm
Weight	85 kg	95 kg
Item no.	15990	60715

