

DOCUMENTS - CTP instructions

CTP INSTRUCTIONS

WE ONLY ACCEPT SEALED WORK AS A COMPOSITE PDF FILE THAT MEETS THE FOLLOWING REQUIREMENTS: 1. Document centering on the page 2. Added cut markers and/or trim box 3. The size of bleeds min. 3 mm on each side 4. In the case of multi-page work, pages in one file, one after another 5. All fonts included or converted to curves 6. The work in CMYK, if RGB elements are detected, the customer shall be informed about this fact 7. In case of finding additional colors, not included in the order, the customer is asked to convert them into CMYK 8. Paths of the die-cutter and UV varnish masks should be included in the composite file with graphics as separate colors with an overprint option 9. The work should be prepared in ISO Coated V2 profile - (Fogra 39) 10. Minimum resolution of raster graphics 300 dpi 11. Maximum sum of colors on paper 320%, on non-absorbent substrates 240% INFORMATION TO BE INCLUDED IN THE WORK DESCRIPTION:

1. Net format of the work
2. Number of pages
3. On which side the work is to be typeset
4. Print ruling, if no information is available, the work will be printed as standard 175 lpi
5. At the customer's request, we can perform the work with a staccato halftone 20 microns
6. Description of the work colors, in case of multi-page work with different colors, please describe each page
7. Detailed description of additional colors
8. Mock-up, can be black and white
9. File path