

master Easy



FULL HD - KVM EXTENDER OVER IP Tune in the easy KVM World

KVM Extender over IP in single DVI, DVI-D,
KVM Extender VGA & KVM Extender USB in CATx

masterEASY single is a highly optimized KVM Extender over IP for distances up to 150m/492ft at a resolution of 1920x1200@60Hz and is available in copper. masterEASY KVM Extender convince with an ultra flat housing - 4 single units in 1RU, have embedded sound and are compatible with standard Network components. Video sharing, USB sharing, multihead.

... masterEASY single CATx

- DVI-D/ USB2.0
KVM Extender over IP
- single in copper/CATx
- max resolution
1920 x 1200 @60 Hz
- max distance 150m/492ft
- 4 single masterEASY KVM Extender in 1RU
- Sound embedded
- Full HD Videos in real time
- USB trnsmission rate max 480Mbit/s
- only one cable for USB & Video
- DVI extension without loss of quality
- Feature - freeze last image
- Local/CPU -Remote/CON Monitor Output
- Single Units :redundant for point to point , in the Matrix Switching System with Switch
- Upgrades: USB & Sound

part. Nr 8112



Single remote



Single local

Let's connect!
KVM can be so simple
kvm-tec

www.kvm-tec.com



All in one go

Matrix Switching Systems up to
56 Endpoints without user system



Bridging - Easy Switching without switch

With **Frontbridging** 2 Local EASYline Extenders can be bridged to 1 remote dual Extender (2 network sockets) & thus one or two screens can display the contents of the PCs simultaneously with different images and can be operated either right or left.

2 local single Unit + 1 remote dual Unit = Bridging on 1 or 2 screens



With **Backbridging** from one dual local extender can be shared to two single remote extenders. For all applications that require monitoring at different locations

1 dual local Unit + 2 remote Units = Bridging or Sharing on 1 or 2 screens



Easy Cross Move - Software feature

both PCs can be operated with one mouse and one keyboard

2 local Units + 1 remote Unit = Easy Cross Move with 1 keyboard & 1 mouse

Switching and VGA included

Technical specifications

		ME1-Local/CPU	ME1-R Remote/CON
Interfaces	Video	1 x DVI in 1x DVI out	2x DVI-D out
	USB 2.0	1 x USB-B to PC	4 x USB-A (devices)
	Audio	1 x 3,5mm jack (Line In) 1 x 3,5mm jack (Line out)	1 x 3,5mm jack Line In) 1Vpp 1 x 3,5mm lack (Speaker) 2x10mW@32Ohm
Video	Signal type	DVI-D	DVI-D
	Resolution (digital)	max. 1920x1200 @ 60Hz	max. 1920x1200 @ 60Hz
Audio	Signal type	DVI-I	DVI-I
	Resolution (analog) (opt.)	max. 1920x1200 @ 60Hz	max. 1920x1200 @ 60Hz
	Color mode	24bit	24bit
Audio	Type	analogue / embedded	analogue/embedded
	Bandwidth	16bit, 44kHz, 2ch	16 bit, 44kHz, 2ch
USB	Specification	USB 2.0	USB 2.0
	Type Rate	transparent max. 480 Mbit/s mass storage devices & camera optional	transparent max. 480 Mbit/s mass storage devices & camera optional
Casing	Material	anodized aluminum	anodized aluminum
	Dimension (w x H x D)	108 x 43 x 107,5 mm	108 x 43x 107,5 mm
	Weight	4.25 x 1.69 x 4,23 inch	4.25 x 1.69 x 4.29 inch
	Shipping weight SET 1895 g /4.17 lb	295 g / 0.65 lb shipment weight 1005g/2,21 lb	295 g/ 0.65 lb shipment weight 890 g/ 1.96lb
Power Supply	Type	wall power supply unit 12 VDC 1A redundant max 35 V	wall power supply unit 12 VDC 1A redundant max 35 V
	Operation	12W	12W without USB devices
Operation environment	Temperature	0 to +45 °C /32 to 113 °F)	0 to +45 °C /32 to 113 °F)
	Humidity	< 80%, non -condensing	< 80%, non- condensing
Storage environment	Temperature	-25 to 80 °C /-13 to 176 F	-25 to 80 °C /-13 to 176 F
	Humidity	< 80%, non condensing	< 80%, non condensing
Cooling		free air convection	free air convection
MTBF		82.820 calculated hours approx. 10 years	82.820 calculated hours approx. 10 years
Conformity		CE, FCC	CE, FCC
Warranty		2 years (5 years optional)	2 years (5 years optional)
Delivery content	Devices	1 x ME1 local (CPU)	1 x ME1 remote (CON)
	Power Supply	1 x wall power supply unit 12V 1A (EU-plug or INT plug)	1 x wall power supply unit 12V 1A (EU-plug or INT plug)
	Cables	1 x DVI - DVI cable 1,8m (5.9ft) 1 x USB cable 1,8m (5.9ft) 1 x VGA-DVI cable 1,8m (5.9ft) opt 1 x Audio cable 1,8m (5.9ft) opt	
	Mounting	4 x rubber feet	4 x rubber feet
	Manual	Quickinstallation manual download: www.kvm-tec	

Part Number & short description

Part.Nr	Order Nr	short description
8112	ME1	masterEASY Extender Single – Set EAN0798190109947 UPC 51497113728
8112L	ME1L	masterEASY Extender Single –Local Unit /CPU EAN 0798190109954 UPC 51497113735
8112R	ME1R	masterEASY Extender Single –Remote Unit /CON EAN 0798190109961 UPC 51497113742
8147	ME-MO	masterEASY USB Memory Upgrade EAN 0798190109244 UPC 051497113025
8141	ME-SO	masterEASY Sound Upgrade EAN 0798190109220 UPC 0798190109220
9003 9002	GV5JU GV5J	Warranty extension to 5 years per UNIT Warranty extension to 5 years per SET
ADD-ONS 6231	UMK-EASY	Rack Mounting Kit for under the table EAN 0798190109466 UPC 051497113247
6232	RMK-EASY-F	Rack Mounting Kit with front panel for EAN 0798190109473 UPC 051497113254
6233	RMK-EASY-FN	Rack Mounting Kit with front panel and Power supply EAN 0798190109480 UPC 051497113261
6234	RMK-EASY	Rack Mounting Kit with front panel and redundand Power supply EAN 0798190109503 UPC 051497113285
6235 6236	DINMK-EASY VH -EASY	Din Rail Mounting EAN 0798190109510 UPC 051497113292 Vesa Mounting EAN 0798190109527 UPC 051497113308

KVM High Performance System FULL HD & 4K KVM Extender



KVM can be so *simple*
Let's connect!
kvm-tec

www.kvm-tec.com