FOODLITE BOOTS



Red Meat Processing

Slaughterhouses

Food Processing

Canneries

A new exceptionally lightweight food industry boot designed for wearer comfort and low temperature performance.

- · Lightweight for increased wearer comfort
- Superb low temperature flexibility down to -40°C
- **Chemically resistant** boot certified to EN 13832-3:2018 (footwear protecting against chemicals)
- Resistant to common **food industry chemicals**, including cleaning, disinfecting and sanitising agents
- · Slip resistant moulded sole
- Cleated outsole for maximum grip
- 200 Joule epoxy coated steel toe cap
- Energy absorbing tunnel system in heel to EN 20345:2011 E
- Ergonomic **cushioned insole** (removable & machine washable) for greater wearer comfort
- Environmentally friendly PVC and Halogen free construction
- Biodegradable & Phalate free
- Seamless construction
- Kick-off lug
- · Adjustable height
- · Knitted nylon lining
- · CE marked on the shaft with date and year of manufacture
- REACH Compliant

Care:

- Machine washable at up to 40°C
- · Shelf life 5 years

Options:

- · Thermal liner
- · Soft-toe version

Certification:

- EN ISO 20345:2011 SB CI SRC E Safety Footwear
- EN 13832-3:2018 N, O, R Chemical Protective Footwear
- **PPE Regulation (EU) 2016/425** Personal Protective Equipment

Sizes:

UK	3	4	5	6	7	8	9	10	11	12	13	14	15
EU	35	36	37	39	41	42	43	44	45	46	47	49	50
US	4	5	6	7	8	9	10	11	12	13	14	15	16

See next page for chemical resistance







FOODLITE BOOTS



Chemical Resistance:

CHEMICAL	CAS NO.	BREAKTHROUGH TIME	CHEMICAL	CAS NO.	BREAKTHROUGH TIME
Ammonia 25%	1336-21-6	> 8 hours	Methanol	67-56-1	> 8 hours
Ammonia Gas	7664-41-7	> 8 hours	Methyl pyrolidone	872-50-4	> 8 hours
Ethanol	64-17-5	> 8 hours	Nitric Acid	7697-37-2	> 32 hours
Ethyl Acetate	141-78-6	> 2 hours	Phosphoric Acid	7664-38-2	> 8 hours
Hexane	110-54-3	> 1 hour	Sodium Hydroxide	1310-73-2	> 32 hours
Isopropanol (IPA)	67-63-0	> 32 hours	Sodium Hypochlorite	7681-52-9	> 8 hours
Lactic Acid	50-21-5	> 8 hours	Toluene	108-88-3	> 1 hour

Breakthrough time is the Normalised Breakthrough time to EN374-3:2003, for more details visit www.workmasterboots.com

Specifications, configurations and colours are subject to change without notice.