

PCA

WIRE MARKING

- Practical combination marking for connected conductors.
- Swift mounting without tools.
- As safe as closed marking.
- According to European standard EN60204.
- Allows alterations on wires already connected, ideal for maintenance.
- Good fastening – narrow width.
- Halogen free.
- Two sizes cater for conductor areas from 0.5 – 6.0 mm².
- Reduced mounting and storage costs.

GENERAL INFORMATION

Design

Open combination marking with locking function.
 Made in strips of semi detached single characters.
 Each size covers a wide diameter range.

Material

Halogen free polyamide 6.6.

Colour

Standard colours yellow and white and international colour code for 0-9.

Print

Hot stamped.

Text

Alphanumeric and special.

Temperature range


From -30°C to +100°C (-22°F to +212°F).

Durability

Excellent resistance to petrol, fats, oils, esters and ketones.

DIMENSIONS IN MM (NOMINAL)

| Type designation | Height (H) | Length (L) | Width (B) | Text height |
|------------------|------------|------------|-----------|-------------|
| PCA10004 | 5 | 9 | 4 | 3 |
| PCA20004 | 5 | 9 | 4 | 3 |



SIZES AND PACKAGINGS

| Article number | Diameter/area/inch | Number of Characters | Pcs./Packaging |
|----------------|---|----------------------|------------------------------------|
| PCA10004PV×&.# | 2.2- 3.6 mm / 0.5- 2.5 mm ² / .087"- .142" | 1 | 320 pcs. = 10 strips of 32 markers |
| PCA20004PV×&.# | 3.6- 6.0 mm / 2.5- 6.0 mm ² / .142"- .236" | 1 | 320 pcs. = 10 strips of 32 markers |

× = Sleeve colour according to the international colour code.

& = Character colour according to the international colour code.

= Character.

N.B! If you wish neutral/blank markers, please exchange the letter »V« to »N«.

APPLICATION

