# ACCESSORIES INK/DOCTORING CUPS



For all "hermetic" standard pad printing machines

Ink/doctoring cup 1-, 2-, 3-colour

Thrust collar 2-colour for "hermetic" pad printing machines  $\emptyset$  90–210 mm

Thrust collar adapter for "hermetic" pad printing machines  $\emptyset$  90 mm

- Scope of supply for all TAMPOPRINT "hermetic" pad printing machines with ink/doctoring cup Ø 30 to 210 mm
- 3 designs: Aluminium, plastics, steel
- Can be used for following cliché types:

Steel, ceramic, Aloxid-special, Magnet-Aloxid-, record-special, Magnet-Screen, Magnet-Aqua, Magnet-Eco, Magnet-microflex clichés, INTAGLIO laser cliché

## Print image sizes:

Ink/doctoring cup  $\emptyset$  60 mm: max.  $\emptyset$  55 mm (SR  $\emptyset$  58 mm) Ink/doctoring cup  $\emptyset$  90 mm: max.  $\emptyset$  85 mm (SR  $\emptyset$  88 mm)

Ink/doctoring cup Ø 130 mm: max. Ø 120 mm Ink/doctoring cup Ø 150 mm: max. Ø 140 mm

Ink/doctoring cup Ø 210 mm: max. Ø 190 mm (SR Ø 200 mm)

# Your advantage:

- ✓ Extensive service/maintenance packages (see below).
- ✓ Ink/doctoring cup at economy price
- ✓ The best ink/doctoring cups in the market



## **Description:**

The following 3 materials are used for the ink/doctoring cups 1-colour  $\emptyset$  30 to 210 mm:

Material	Machine series	Ø Ink/doctoring cup				
Plastics	all standard machine series (ENCODER with additional thrust collar)	60, 90 mm				
Steel	ENCODER	30, 40, 60 mm				
Aluminium	all standard machine series	60–210 mm				

#### Service offers:

#### ✓ Plastic ink/doctoring cups

Exchange of the customer ink/doctoring cup against calculation.

Mechanical lapping (only possible if there are no damages on the doctoring lip).

#### ✓ Aluminium ink/doctoring cups

Exchange + mechanical lapping of doctoring lip + sealing ring.

#### √ Steel ink/doctoring cups

Exchange of doctoring lip + mechanical lapping.

If doctoring lips are fully worn (contact surface wider than 0,3 mm) an exchange of the doctoring ring is basically recommended.

#### ✓ Non-binding quotation

Please send us your ink/doctoring cup. We will check it free of charge and will send you a non-binding quotation.

Overview of all ink/doctoring cups 1-colour see page 8



- In TAMPOPRINT "hermetic" pad printing machines with ink/doctoring cup Ø 60 mm and Ø 90 mm
- Can be used for following cliché types: Steel, ceramic, Aloxid-special, Magnet-Aloxid-, record-special, Magnet-Screen, Magnet-Aqua, Magnet-Eco, Magnet-microflex clichés, INTAGLIO laser cliché

#### Print image size:

Ink/doctoring cup  $\emptyset$  60 mm: max.  $\emptyset$  55 mm Ink/doctoring cup  $\emptyset$  90 mm: max.  $\emptyset$  85 mm

## Your advantage:

- ✓ Immediate check of the ink condition
- ✓ Ink/doctoring cup can be opened while it is still in the machine
- ✓ Re-filling of ink into ink/doctoring cup while it is still in the machine
- ✓ ClipLock® closure uses the complete ink/doctoring cup diameter as an opening
- ✓ Improved economy of set-up time and ink consumption
- ✓ Downtimes during production will be considerably reduced
- ✓ Extensive service/maintenance package (see below)
- ✓ Glass stirring staff and solvent pipette included in delivery
- ✓ Easy handling with gripper for lid





## **Description:**

2 materials are used for the ink/doctoring cups ClipLock® 1-colour Ø 60 mm to 140 mm.

Material	Machine series	Ø Ink/doctoring cup
Plastics	Series CONCENTRA, HERMETIC 6-12, RAPID, SEALED INK CUP E, TSQ, TSM, V-DUO	60, 90 mm
Aluminium	all standard machine series	130, 140 mm

#### Spare parts:

opulo pullo.	
Lid ClipLock® Ø 60 mm	Item No. 09 01 65
Lid ClipLock® Ø 90 mm	Item No. 09 01 66
Lid ClipLock® Ø 130 mm	Item No. 09 09 22
Lid ClipLock® Ø 140 mm	Item No. 09 09 22
Glass stirring staff	Item No. 09 01 69
Solvent pipette	Item No. 09 01 75

#### Option:

## Service offers:

#### ✓ Plastic ink/doctoring cups

Mechanical lapping (only possible if there are no damages on the doctoring lip).

#### ✓ Non-binding quotation

Please send us your ink/doctoring cup. We will check it free of charge and will send you a non-binding quotation.

Overview of all ink/doctoring cups 1-colour see page 8



- In all TAMPOPRINT "hermetic" pad printing machines with ink/doctoring cup Ø 60 mm and Ø 90 mm
- Can be used for following cliché types:

Steel, ceramic, \*Aloxid-special, Magnet-Aloxid, \*record-special, \*Magnet-Screen, \*Magnet-Aqua, \*Magnet-Eco, Magnet-microflex clichés, \*INTAGLIO laser cliché (\* When using these cliché types the lifetime of the clichés may be limited)

#### Print image sizes:

Ink/doctoring cup  $\emptyset$  60 mm: print image size max.  $\emptyset$  55 mm Ink/doctoring cup  $\emptyset$  90 mm: print image size max.  $\emptyset$  85 mm Non-printing area around the centre bar approx. 5 mm

# Your advantage:

- ✓ 2 different-coloured print images (side by side) in one printing process with a 1-colour "hermetic" pad printing machine.
- ✓ Extensive service/maintenance package (see below).



# **Description:**

#### The ink/doctoring cup 2-colour Ø 60 mm

consists of a steel base body with an attached doctoring lip made of sintered metal, eroded from solid material, and a centered separating web.

## The ink/doctoring cup 2-colour Ø 90 mm

is an aluminium base body with our well-tried doctoring lip made of sintered metal. The ink separation takes place via a separately inserted aluminium separating web with an exchangeable plastic doctoring lip. If the doctoring ring or doctoring lip are wearing down, they can be exchanged at TAMPOPRINT.

# Service offers:

- ✓ Ink/doctoring cup Ø 60 mm
  - Exchange of hard metal doctoring lip + mechanical lapping.
- √ Ink/doctoring cup Ø 90 mm
  - Exchange of doctoring ring + hard metal doctoring lip + mechanical lapping.
- If doctoring lips are fully worn (contact surface wider than 0,3 mm) an exchange of the doctoring ring is basically recommended.

## **Accessories required:**

Thrust collar multicolour Ø 90 mm Item No. 09 01 27 Ink/doctoring cup 2-colour Ø 90 mm, aluminium Item No. 09 00 58



- In all TAMPOPRINT "hermetic" pad printing machines with ink/doctoring cup Ø 60 mm
- Can be used for following cliché types:

Steel, ceramic, \*Aloxid-special, Magnet-Aloxid, \*record-special, \*Magnet-Screen, \*Magnet-Aqua, \*Magnet-Eco, Magnet-microflex clichés, \*INTAGLIO laser cliché (\* When using these cliché types the lifetime of the clichés may be limited)

Print image size:

Ink/doctoring cup  $\emptyset$  60 mm: print image max. 3x 15 mm wide with 5 mm intermediate distance

# Your advantage:

- ✓ 3 different-coloured print images (side by side) in one printing process with a 1-colour "hermetic" pad printing machine.
- ✓ Extensive service/maintenance package (see below).




## **Description:**

The ink/doctoring cup 3-colour  $\emptyset$  60 mm corresponds in its basic concept and material with the two-colour ink/doctoring cup  $\emptyset$  60 mm. The separation of the ink compartments, however, takes place by means of two separating webs. The doctoring lip is a one-piece doctoring ring with two separating webs.

#### **Service offers:**

- ✓ Exchange of hard metal doctoring lip + mechanical lapping
- ✓ If doctoring lips are fully worn (contact surface wider than 0,3 mm) an exchange of the doctoring ring is basically recommended.



#### **Accessories required:**

Thrust collar multicolour Ø 60 mm Item No. 09 00 86 Ink/doctoring cup 3-colour Ø 60 mm, steel Item No. 09 00 22

Item No. 09 00 72 (included in delivery of standard machine) Item No. 09 00 62 (included in delivery of standard machine)



- Use of an ink/doctoring cup Ø 60 mm in a pad printing machine with ink/doctoring cup size Ø 90 mm
- Can be used for following clichés:

Steel, ceramic, Aloxid-special, Magnet-Aloxid-, record-special, Magnet-Screen, Magnet-Aqua, Magnet-Eco, Magnet-microflex clichés, INTAGLIO laser cliché

# Your advantage:

- ✓ Your print image is often smaller than 55 mm
- ✓ Print image centre is identical with 90 mm ink/doctoring cup
- ✓ Smaller ink/doctoring cup reduction of ink waste
- ✓ Your cliché size remains the same
- ✓ Special solutions for deviations from print image centres possible
- ✓ Ink filling capacity is clearly reduced
- ✓ Reduction of disposal costs if 2-component ink is used
- ✓ The gripping tongs and assembly table which are included in delivery can still be used. No necessity to purchase new ones.



# **Description:**

The thrust ring is designed for a TAMPOPRINT plastic ink/doctoring cup.

Note:

You can continue to use the gripping tongs and assembly table which are included in delivery.

No necessity to purchase new ones.

#### **Accessories required:**

Thrust collar adapter Ø 90 m ltem No. 09 01 37 lnk/doctoring cup Ø 60 mm, plastics ltem No. 09 00 29



■ In "hermetic" pad printing machine with ink/doctoring cup Ø 90 to 210 mm

#### Can be used for following clichés:

Steel, ceramic, Aloxid-special, Magnet-Aloxid-, record-special, Magnet-Screen, Magnet-Aqua, Magnet-Eco, Magnet-microflex clichés, INTAGLIO laser cliché

#### Print image size:

Ink/doctoring cup Ø 30 mm: print image 2x max. Ø 25 mm Ink/doctoring cup Ø 60 mm: print image 2x max. Ø 55 mm Ink/doctoring cup Ø 90 mm: print image 2x max. Ø 85 mm Note:


Non-printing area between the ink/doctoring cups: see table down to the right.

# Your advantage:


- ✓ 2 different-coloured print images (side by side) in one printing process with a 1-colour "hermetic" pad printing machine.
- ✓ 2 ink/doctoring cups positioned side by side by using our 2-colour thrust collar.




Thrust collar for 2x ink/doctoring cup Ø 30 mm



Thrust collar for 2x ink/doctoring cup  $\emptyset$  60 mm



Thrust collar for 2x ink/doctoring cup  $\emptyset$  90 mm



## Non-printing area

Machine type with the following ink/doctoring cup size	Machine type cliché size depth x width	Thrust collar for the following ink/doctoring cups	Non-printing area between the two ink/doctoring cups		
Ø 90	100 x 215 mm	2 x Ø 30 mm	19 mm		
Ø 130	150 x 300 mm	2 x Ø 60 mm	15 mm		
TSQ Ø 90	440 x 100 mm	2 x Ø 30 mm	19 mm		
TSQ Ø 90	600 x 100 mm	2 x Ø 30 mm	19 mm		
TSQ Ø 90	800 x 100 mm	2 x Ø 30 mm	19 mm		
TSQ Ø 130	730 x 150 mm	2 x Ø 60 mm	15 mm		
TSQ Ø 130	930 x 150 mm	2 x Ø 60 mm	15 mm		
TSG Ø 210	220 x 500 mm	2 x Ø 90 mm	33 mm		
TSM 60/90 universal transverse doctor kit	100 x 440/600/800	2 x Ø 30 mm	19 mm		
TSM 130 universal transverse doctor kit	150 x 730/930	2 x Ø 60 mm	15 mm		
TSM 60/90 universal multiple colour kit Solo	100 x 215	2 x Ø 30 mm	19 mm		

# **Accessories required:**

Thrust collar 2-colour Ø Ø 30 mm	Item No.	09 01 35
2 ink/doctoring cups Ø 30 mm, steel	Item No.	09 00 01
Gripping tongs 2-colour Ø 30 mm	Item No.	09 01 43
Assembly table 2-colour Ø 30 mm	Item No.	09 01 52
,		
Thrust collar 2-colour Ø 60 mm	Itom No	09 01 36
miusi coliul 2-coloul & 60 mm	Helli NO.	09 01 30
2 ink/doctoring cups Ø 60 mm, steel	Item No.	09 00 03
Gripping tongs 2-colour Ø 60 mm	Item No.	09 01 44
Assembly table 2-colour Ø 60 mm	Item No.	09 01 53
,		
Thrust collar 2-colour Ø 90 mm	Itom No	09 01 39
2 ink/doctoring cups Ø 90 mm, plastics	Item No.	09 00 31
Gripping tongs 2-colour Ø 90 mm	Item No.	09 01 45
Assembly table 2-colour Ø 90 mm	Item No.	09 01 54

# Overview 1-colour standard ink/doctoring cups

	Ink/ doctoring cup	Steel	Steel with bellows	Steel with plastic piston + sealing rings	Aluminium with carbide doctoring ring	Alumini- um with ceramic doctoring ring	ClipLock® Aluminium mit Deckel	Plastic with carbide doctoring ring	Plastic with ceramic doctoring ring	ClipLock® Aluminium with lid	Thrust collars 1-colour	Gripping tongs Grippers for lid <sup>3)</sup>	Assembly tables
	Ø mm	Item No.	Item No.	Item No.	Item No.	Item No.	Item No.	Item No.	Item No.	Item No.	Item No.	Item No.	Item No.
	Ø 30	09 00 01	-	-	-	_	_	-	_	-	_	-	_
O D E R	Ø 40	09 00 02 09 00 13 Height 39 mm	09 00 04 (Pneumotic supply at the top) 09 00 06 (Pneumotic supply on the side)	-	-	-	-	-	-	-	09 00 81	09 00 71	09 00 61
N N	Ø 60	09 00 03	09 00 05 (Pneumatic supply at the top) 09 00 07 (Pneumatic supply on the side)	09 00 17	-	-	-	-	-	-	09 00 82	09 00 72	09 00 62
	Ø 60	-	_	-	09 00 20 09 00 52 <sup>2)</sup>	09 02 322)	-	09 00 292)	09 00 322)	09 00 332)	09 00 89	09 00 72	09 00 62
	Ø 60 SR <sup>1)</sup>	-	-	-	-	-	-	09 00 402)	-	-	09 00 87	09 00 72	09 00 62
	Ø 90	-	-	-	09 00 30 09 00 53 <sup>2)</sup>	09 02 332)	-	09 00 312)	-	09 01 342)	09 00 84	09 00 73 09 01 67 <sup>3)</sup>	09 00 62
	Ø 90 SR <sup>1)</sup>	_	_	-	-	_	_	09 00 412)	_	_	09 00 79	09 00 73	09 00 63
	Ø 130	-	-	-	09 00 50 09 00 51 <sup>2)</sup>	-	09 00 382)	-	-	-	09 00 85	09 00 74 09 00 68 <sup>3)</sup>	09 00 64
	Ø 140	-	-	-	09 00 542)	09 02 442)	09 00 392)	-	-	-	09 00 77	09 00 70	09 00 66
	Ø 150	-	-	-	09 00 552)	-	-	-	-	-	09 00 78	09 00 76	09 00 65
	Ø 210	-	-	-	09 00 572)	-	-	-	-	-	09 01 26	09 00 69	09 00 67
	Ø 210 SR <sup>1)</sup>	-	-	-	09 00 492)	-	-	-	-	-	09 01 26	09 00 69	09 00 67

SR1) = Doctoring lip mirrored, therefore print image diameter increased by approx. 3 mm (Doctoring lip chamfered from inside outwards for increased printing area)

Please note when placing a repeat order: The article number of your ink/doctoring cup is marked on the top side of the ink/doctoring cup.



## TAMPOPRINT® GmbH

Lingwiesenstraße 1

70825 Korntal-Münchingen, GERMANY

449 7150 928-0
Fax: +49 7150 928-400
E-Mail: info@tampoprint.de
Ventes et Affaires Françaises
+49 7150 928-144

Fax: +49 7150 928-432 E-Mail: ventes@tampoprint.de http: www.tampoprint.de

#### TAMPOPRINT® INTERNATIONAL CORP.

1400 26th Street, Vero Beach, FL 32960, USA © +1 772 778-8896, 800 810-8896

Fax: +1 772 778-8289 E-Mail: info@tampoprint.com http: www.tampoprint.com

## TAMPOPRINT® IBERIA S.A.U.

Polígono Industrial Martorelles, C/ Sant Martí, s/n (entre Gorgs y Mogent) 08107 Martorelles (Barcelona), SPAIN

© +34 93 2327161
Fax: +34 93 2471500
E-Mail: tampoprint@tampoprint.es
http: www.tampoprint.es



The reproduction of trademarks and brands used in this brochure, even if not explicitly expressed, does not justify the assumption that such names or symbols may be considered as free as defined by the Trademark Act and may therefore freely be used. The rights are the property of the respective owner.

TAMPOPRINT products are permanently updated to keep pace with the latest technological developments. For this reason, figures and descriptions are non-binding. Manufactured according to EC Directive 98/37/EC.

Subject to alterations! @Copyright

<sup>&</sup>lt;sup>2)</sup> = 30° - chamfered thrust collar contact surface

<sup>3) =</sup> for ClipLock®