fako® Polishing paste 9311



UFI № VDST-T0GU-T006-XHHX



TDS 4200

Acrylic glass is a noble material that is characterised by a number of special properties: practical ones such as resistance to breakage, resistance to ageing and light transmission as well as aesthetic ones such as transparency and beauty of the surface. Obviously a special material requires professional care. Our care products specially developed for Plexiglas help you to maintain the beauty and value of the material for years and decades. In comparison to silicate glass, two properties must be taken into particular consideration when caring for and cleaning acrylic glass. On the one hand the lower surface hardness and therefore higher susceptibility to scratches of acrylic glass, on the other hand the susceptibility of acrylic glass to solvents, especially organic ones. The use of incompatible polishing materials can cause stress cracks and matt surfaces.



With fako® Polishing paste 9311 a care product is available, which is specially developed for the properties of Plexiglas, other acrylic glass and plastics

Properties	Data
NSN	7930-12-124-2497 C3910
Effect	Matt surfaces become clear again, scratches and scrapes are removed. Unsightly panes become flawless again! The treatment process is quite simple.
Application	Clean dirty surfaces with clear lukewarm water and a clean, soft viscose sponge until adhering dirt is removed. Put some fako ® Polishing paste 9311 with lint-free fako ® special polishing cloth on the moistened surface and polish under pressure in circular movements until the surface is dry. Polish to a gloss with another dry fako® special polishing cloth until the residues are removed and the surface is dry and clear. For machine application work in small sections of approx. 20 cm. Apply fako® Polishing paste 9311 to the wet surface cleaned with water and distribute with the polishing pad before starting the machine. Polish slowly rotating with low pressure in even circles. Reduce the pressure when the fako® Polishing paste 9311 dries out or keep the surface moist during the polishing process by spraying it with water. Use lint-free soft polishing pad.
	When removing deep scratches, the polishing process may cause matt spots. In this case we recommend an after-treatment with fako® Polishing milk 9322
Packaging / delivery form	90 g tubes, 25 tubes pro cardboard box

Hazard statement and safety advice

✓ Read the label before use. EUH rates must be observed.

Handling and storage

- ✓ Keep a tube tightly closed. Use only with good ventilation. Ensure good room ventilation also in the floor area (vapours are heavier than air). Store at temperatures between 10° and 20°C, protect from sunlight and heat. Always close the tube after use. Please keep the tube cap clean.
- ✓ Minimum shelf life 24 months after production at room temperature.

Exclusion of liability

- ✓ This product information is based on the latest state of our knowledge and does not exempt the user from carrying out his own tests or taking his own precautions. We do not accept any liability for results from suggested applications, as conditions may change depending on the type of application.
- To the extent an exclusion of liability is permitted by law, the CBG Composites GmbH will not be liable for any loss or damage arising from this product, whether direct, indirect, special, incidental or consequential, regardless of the legal basis asserted, including warranty, contact, negligence or strict liability.

Subject to modifications



CBG Composites GmbH Egerpohl 2 D-51688 Wipperfürth / Germany

Tel: 02267-67-0 Fax: 02267-67-222



www.fako.de, www.cbg-composites.de info@cbg-composites.de

