Straight Conveyor

Enquiry Form

Customer Information

Company Name:	
Contact:	
Email Address:	
End User:	
Date:	
Telephone No:	

How much are you thinking about spending on this part of your project?	
When are you thinking about start up? Is this for CapEx planning or an immediate need?	

Product Information

Product:		Product Loading:	Kg/m^2
Size & Shape:		Environmental Temperature :	^oC
Characteristics:	Wet **O** Moist **O** Dry **O** / Soft **O** Firm **O**	Product Temperature:	^oC

Conveyor Information

Belt Width:	mm	Belt Type/Mesh :	
Conveyor Length:	mm overall	Standard Belt Height (970 mm +/- 50mm) :	Yes **O** No **O**
Belt Speed/Range:	Metres per Minute	Castors:	Yes **O** No **O**

Note — If non-standard height, or incline/decline is required, please specify in comments section (Include flight details, if necessary)

Drive and Control Options

Electrical Supply:		Motor Required:		Variable Frequency Device (VFD):	
Voltage	V	Standard SEW SA37	Yes **O** No **O**	Control Panel	Yes **O** No **O**
Frequency	Hz	SEW XCO SA37	Yes **O** No **O**	Invertek Optidrive E3	Yes **O** No **O**
Phase	Ph	St/Steel SEW	Yes **O** No **O**	None	Yes **O** No **O**
		None	Yes **O** No **O**		

Hygienic Upgrades

Hygienic Bolt Fixings:	Yes **O** No **O**	Sealed Foot Bracket (Not available with castors)	Yes **O** No **O**

As standard, motor and VFD are mounted on right hand side of conveyor, when viewed from infeed.

All electrical components are rated for IP66 Ingress Protection. As supplied, conveyor is deemed to be a non-workstation unit .

Comments/Special Requirements