



REV	MODIFICATION	DATE	DRAW

NOTES:
 SPECIFICATION:
 1.Current Rating: 3A
 2.Withstanding Voltage: 800 VAC (1 Minute)
 3.Insulation Resistance: 1000 Megohms Min.
 4.Contact Resistance: 30 Milliohms Max.
 5.Operation Temperature: -40°C to +85°C
 6.Retention Force: 750 g Min.

MATERIAL:
 1.Contact:Brass 0.64mm Square Pin
 2.Insulator: P.B.T. + 30% G.F.
 3.Plated: Gold Flash

ORDERING INFORMATION:
 MPHMB-2 XX XX BE102G760
 NO. OF CONTACT — PLATING
 01:G/F

DIMENSION IN mm [Inch]		PROD. SPEC.	KINGFONT PRECISION INDUSTRIAL CO., LTD.	
TOLERANCE UNLESS OTHERWISE SPECIFIED		PKG. SPEC.	TITLE HEADER MALE 2.54mm D/R SMT CUSTOMER DRAWING	
.X±0.30	X'±	APPROVE <i>Gum</i>	FILE NO.	DWG NO. MPHMB-2XXXXBE102G760
.XX±0.20	.X'±	CHECK <i>Tony</i>	SIZE A4	PROJ. SHEET 1 / 1
.XXX±	.XX'±	DRAW <i>Sam</i>	SCALE 4:1	REV A

P.C.B LAYOUT