

PURION PRO MULTIPLANT 2500 / 8



The PURION PRO MULTIPLAN 2500 / 8 is designed for UV based disinfection in case of high flow rates and special liquids with very low transmission. The electric control cabinet can be equipped with the Operating Time Counter (OTC 2). The potential free contact D1-D2 (error sum signal) enables easy integration into existing monitoring systems.

applications / PURION PRO MULTIPLANTS are suitable for:

- coolant/ lubricant
- circulation water from washing processes
- applications in agriculture

options for configuration

hot water up to 90 °C

Operating Time Counter OTC 2

product line	PURION PRO MULTIPLANT 2500 / 8
flow rate for given UVC-transmission	> 20 % T _{1cm} : 20 m ³ /h > 10 % T _{1cm} : 7 m ³ /h
dosis	400 J/m ²
dimension (L x B x H mm)	approx. 600 x 400 x 1.200
weight	85 kg
no. of lamps	8
max. operating pressure	10 bar
electrical connection	PURION controll cabinet Model 1: • 3 ~/N/PE 50 Hz 400/230V • L/N/PE 50 Hz 230V
total power	8 x 90 W or 8 x 106 W (depends on configuration)
current protection	3 x 6A
rack	grooved aluminium



article number: 130 12100 0000
article number: 130 12500 0000

- water up to 40 °C
- hot water up to 90 °C
Operating Time Counter (OTC 2)



article number: 130 12200 0000
article number: 130 12600 0000

- water up to 40 °C
- hot water up to 90 °C
Operating Time Counter (OTC 2)



article number: 130 12300 0000
article number: 130 12700 0000

- water up to 40 °C
- hot water up to 90 °C
Operating Time Counter (OTC 2)



article number: 130 12400 0000
article number: 130 12800 0000

- water up to 40 °C
- hot water up to 90 °C
Operating Time Counter (OTC 2)

equipment PURION MULTIPLANT 2500 / 8

Service-Kit
article number: 292 00900 0000



PURION UV-lamp 90 W
article number: 200 00600 0000



PURION UV-lamp 106 W
article number: 200 00800 0000

