

Technical and general information



The new generation of service and maintenance plugs.

Plugtite hygiene is specially manufactured from a rubber compound that is FDA approved for use in the food and beverage processing Industry.

The use of the plug helps to ensure that sensitive working areas are kept free of contamination from oils, other liquids and product residue by preventing leakage and contamination when cleaning and servicing equipment. Also used in the storage and transit of processed products.

MADE FROM A SPECIAL COMPOUND IN OUR OWN FACTORY

The Plugtite aperture has been designed and engineered to give the plug greater compression than standard solid plugs ensuring a perfect seal whilst still being able to cut to size if needed.

- Greater resistant to most oils within temperature range from -25°C up to 90°C
- O Does not shrink, leak or discolor
- Resistant to sunlight for greater shelf life, does not split/crack or deteriorate
- ② Easy to use. Insert, squeeze, press home and release
- The compressed rubber ensures a tight fit

3 STANDARD APERTURES

2mm - 14mm
5mm - 24mm
15mm - 45mm

OTHER MEMBERS OF THE PLUGTITE FAMILY

Plugtite Heat

For use in operations such as **Electrostatic lines**, die casting etc. where high **heat resistance** is a requirement. More detailed information is available on our Plugtite Heat product sheet.

Plugtite Industrial

For use in the service/maintenance of industrial machinery such as hydraulic/chemical linesand Industrial. More detailed information is available on our Plugtite Industrial product sheet