SANDSTRAHLEN VON A-Z

Aqua Blast

The AQUA BLAST wet blasting cabinet is a combination system for degreasing and simultaneous gentle beams of various workpieces. The water - jet mixture is housed in the cabin swamp. This abrasive mixture is sucked in via a novel centrifugal pump of wear-resistant polyurethane. At the jet of compressed air is additionally adjustable added so as to achieve an optimum surface finish. After loading of the workpiece, the blasting medium mixture flows back into the cabin sump and is thus an abrasive circuit ensured. Battered fine abrasive is suspended from the cab sump and fed to a band filter on the cabin back.

Advantages of the wet blasting method:

- Dust-free process
- friendly surface treatment
- Simultaneous degreasing and radiation
- Water serves as a lubricant between the workpiece and blasting agent
- Low consumption of blasting agent
- preventing roughness on soft surfaces

Typical applications:

- Degreasing / surface finish of workpieces in derFahrzeug-, aerospace and plastics industry
- Cleaning of molds and tools removing paint, rust, carbonates, oil slag
- surface preparation
- Satin gloss finish stainless steel u. other metals
- Deburring machine parts etc.



example AQUA BLAST 915



example AQUA BLAST









Good visibility through windscreen wipers and Wasserspüleinrichtung. Safety glass. Wear-blasting guns, very light. Interchangeable nozzles of silicon carbide or boron carbide.

Service-friendly complete with pump, removable motor 2,2 kW / 2800 rpm.

Quick-change, wear-resistant centrifugal pump made of polyurethane with stainless steel filter



SANDSTRAHLEN VON A-Z

Technical specifications

Dimensions: W x T x H

model 915
 model 1215
 model 1515
 915 x 880 x 1891
 1215 x 1180 x 1891
 1515 x 1480 x 2041

Electrical: 430 volt three-phase

or 230 volts

Compressed air: 7 bar, 1.14 m³ / Min / connection. ½ "

Water: 2 - 6 bar / Connection: ½ "

Sewage: 10 l / min.

Ventilation: 110 mm

Blasting material stock:

model 915
model 1215
model 1515
50 I of water, abrasives 15 kg
100 I of water, abrasives 25 kg
150 I of water, abrasives 25 kg

Werkgutgewicht:

model 915
 model 1215
 model 1515
 80/100 kg
 250 kg

Price, special applications and special equipment on request.