

Technical data sheet

Injection mortar in cartridge, 280 ml

Item no. 3497800



Styrene-free, vinyl ester composite mortar for spread-free anchoring of high loads with threaded anchor rods. Coaxial cartridge, including 1 mixing tube, to be worked with the standard cartridge gun or VM-P 345 Profi.

European Technical Assessment for cracked and uncracked concrete, as well as for masonry of full and hollow brick. Earthquake-proof in concrete according to Category C1. Fire protection approval for concrete and masonry with fire resistance classes up to 120 minutes.

Substrate temperature during processing -10 °C to +40 °C (concrete), ambient temperature after complete hardening -40 °C to +120 °C (in concrete). Will keep for at least 18 months if stored in a dark, cool and dry place.

Additional product text 2	The injection mortar has a European Technical Approval (ETA) for cracked and uncracked concrete, as well as for masonry of full or hollow brick. It is earthquake-proof according to performance category C1 and has fire protection approvals for concrete and masonry with a fire resistance class up to 120 minutes.
Product text, scope of delivery	The injection mortar is worked with a pressing gun, type VM-P 345 Profi, or a standard silicone press. The substrate temperature during processing must be -10 °C to +40 °C (concrete) and the ambient temperature after complete hardening -40 °C to +120 °C (in concrete). If stored in a dark, cool and dry place, the mortar will keep for at least 18 months. The injection mortar VMU is supplied in cartridges with a volume of 280 ml or 420 ml, including a mixing tube.

Master data

Item no.	3497800
Type	VMU plus 280
Description 1	Injection mortar
Description 2	in cartridge
Dimension	280ml
Smallest sales unit	1,00 Piece
Weight	56,00 kg/100 pc.

Technical data

Adhesive application	Construction/mounting
Hardening method	2-component
Contents	280,00 ml
With brush	<input type="checkbox"/>
Delivery form	Cartridge
Transparent	<input type="checkbox"/>