#### TECHNICAL SHEET

## ADJUSTABLE PEDESTAL 40/60 MM

PAVING









# UNIKA adjustable pedestal 40/60mm

Discover the most efficient solution for any slab terrace installation. The UNIKA pedestal is height-adjustable from 40 to 60 mm. It can be raised to a height of up to 1 meter using the extension accessory. The height can be easily adjusted to the nearest millimeter using the adjustment ring: from the top by using the YEED Tightening key, or manually from the side.

The UNIKA pedestal is an all-in-one revolution: the noise buffer accessory is integrated directly onto the pedestal head, and the red clamping ring makes the head self-levelling or fixed.

Note: always calculate the height to catch up by deducting the thickness of the covering to obtain the required pedestal size.

## Application & use

Creation of terraces in porcelain stoneware, stone, concrete or gratings for pedestrian use.

The installation on pedestals requires the use of a covering with a minimum thickness of 2cm. It is possible to use tiles (porcelain stoneware), concrete slabs, reconstituted or rectified natural stone (5cm thick)

#### Technical characteristics

Composition: polypropylene (recycled and recyclable)

Color: black and red\*

Origin: France

Garantee: 10 years

Conformity: norm DTU 43.1

Use: pedestrian only

Weight: 284g

Base dimension: 200 mm x 200 mm

**Head diameter:** 142 mm

Lugs: Height 8 mm / Thickness 4 mm

Resistance to temperatures: from -40°C to +60°C Resistance to atmospherique agents: UV and frost

Load resistance: up to 1 ton

### Product benefits

- + Easier and faster to use
- + Square and pre-cut base plate, which adapts perfectly to corners and angles
- + Height adjustment on the side manually and on top with the YEED tightening key
- + Integrated noise buffer
- Self-leveling or fixed pedestal head
- + 4 removable lugs for easy installation
- + Compatible accessories UNIKA 20, 60 and 120 mm extension
  - YEED tightening key