

## MC AND MCL SERIES

### Technical specifications

Model		MC2-300	MC2-400	MC2-600	MC2-800	MC2-1000
Press capacity	kN	3,000	4,000	6,000	8,000	10,000
	US t	340	450	675	900	1,125
Stroke rate	1/min	25-80	15-70	15-60	15-50	15-45
Stroke length	mm	250	350	350	350	350
	in	9.8	13.8	13.8	13.8	13.8
Slide adjustment	mm	150	200	250	250	300
	in	5.9	7.9	9.8	9.8	11.8
Die height*	mm	550	600	800	800	900
	in	21.7	23.8	31.5	31.5	35.4
Slide dimensions	mm	2,600 x 1,000	2,800 x 1,300	4,000 x 1,500	4,000 x 1,500	4,000 x 1,500
	in	102.4 x 39.4	110.2 x 52.1	157.5 x 59.1	157.5 x 59.1	157.5 x 59.1
Bolster dimensions	mm	2,700 x 1,100	2,800 x 1,300	4,000 x 1,500	4,000 x 1,500	4,000 x 1,500
	in	106.3 x 43.3	110.2 x 52.1	157.5 x 59.1	157.5 x 59.1	157.5 x 59.1

\*Slide stroke down, adjustment up (SDAU) | All models in 2-point design | Metric specifications are binding | Subject to technical modifications

Model		MCL2-200	MCL2-300	MCL2-400	MCL2-600	MCL2-800
Press capacity	kN	2,000	3,000	4,000	6,000	8,000
	US t	225	340	450	675	900
Stroke rate	1/min	35-70	20-40	20-40	15-50	15-40
Stroke length	mm	150	250	300	350	350
	in	5.9	9.8	11.8	13.8	13.8
Slide adjustment	mm	120	120	150	250	250
	in	4.7	4.7	5.9	9.8	9.8
Die height*	mm	450	600	700	800	800
	in	17.7	23.6	27.6	31.5	31.5
Slide dimensions	mm	1,850 x 650	2,600 x 1,000	2,800 x 1,300	4,000 x 1,500	4,000 x 1,500
	in	72.8 x 25.6	102.4 x 39.4	110.2 x 52.1	157.5 x 59.1	157.5 x 59.1
Bolster dimensions	mm	1,850 x 850	2,600 x 1,100	2,800 x 1,300	4,000 x 1,500	4,000 x 1,500
	in	72.8 x 33.5	102.4 x 43.3	110.2 x 52.1	157.5 x 59.1	157.5 x 59.1

\*Slide stroke down, adjustment up (SDAU) | All models in 2-point design | Metric specifications are binding | Subject to technical modifications