

#### Managed Industrial switch

> 4 ports 802.3bt PoE      > 2 SFP/1G + 1 TP/1G Uplink      > G.8032 ERPSv2 Ring protection      > 2 DI | 2 DO

The NSBox access Nodes are devised for the deployment of protected outdoor Video Surveillance systems. The Nodes provide trouble proof operation of connected video cameras with a secure power supply, reliable data transmission, and protection of sensitive equipment from surges caused by lightning and power fluctuations. It is a perfect technology solution for time and money saving in any outdoor Video Surveillance projects for a large-scale area ranging from construction sites, parking lots, hotels, parks, shopping mall, sports facilities, airports, railways, bridges, and highways.

The basic equipment of the NSBox-2041 includes: wall mounting brackets, mounting plate with DIN-rails, terminal blocks, a two-pole circuit breaker, an electrical grounding bar, a fan with a thermostat, a set of cable glands. These modules can also be included in the assembly:

- Managed Industrial switch: uplink 2 SFP/1G + 1 TP/1G, 4 ports TP/1G PoE 802.3bt, G.8032 ERPSv2, DI/DO;
- Power Supply 55VDC-360W or UPS NR-48VDC-360VA with mounting kit for batteries 7Ah x4;
- Climatic control system inside enclosure: thermostats, Fan Heater, Thermoelectric Cooler/ Assembly;
- Fibre-optic distribution frame (ODF), complete with SC/LC adapters, pigtails, patch cords, and a mounting kit;
- Lightning and surge protection for Ethernet PoE ports and power circuits 220VAC.

The basic NSBox-2041 models are: NSBox-2041 | NSBox-2041H | NSBox-2041R | NSBox-2041HR

NSBox-2041 PX14F34F	Access Node: NSB-3040F1 enclosure with Fan, without Heater, with ODF; 55VDC-360W Power supply; NIS-3500-3204PGE Switch: uplink 2 SFP/1G + 1 TP/1G, 4 ports TP/1G PoE 802.3bt (95W); Reboot PDs
NSBox-2041H PX14F34H	Access Node: NSB-3040H1F1 enclosure with Fan Heater, with ODF; 55VDC-360W Power supply; NIS-3500-3204PGE Switch: uplink 2 SFP/1G + 1 TP/1G, 4 ports TP/1G PoE 802.3bt (95W); Reboot PDs
NSBox-2041R RX14F38F	Access Node: NSB-3838F1 enclosure with Fan, without Heater; UPS NR-48VDC-360VA with mounting kit for batteries 7Ah x4; NIS-3500-3204PGE Switch: uplink 2 SFP/1G + 1 TP/1G, 4 ports TP/1G PoE 802.3bt (95W)
NSBox-2041HR RX14F38H	Access Node: NSB-3838H1F1 enclosure with Fan Heater; UPS NR-48VDC-360VA with mounting kit for batteries 7Ah x4; NIS-3500-3204PGE Switch: uplink 2 SFP/1G + 1 TP/1G, 4 ports TP/1G PoE 802.3bt (95W)

#### Technical Data



Input Voltage   Power consumption	: 100 - 240VAC   500 W (no more)
Enclosure material (cabinet, door)	: Sheet steel, powder-coated, primed
Protection category IP/NEMA   IK Code	: IP66 / NEMA4   IK08
Enclosure mounts	: Wall or pole mount with NSBon-01 kit
Operating temp.   with thermal insulation	: -40°C to +60°C   -50°C to +60°C
Dimensions (no cable glands)	: 300x400x210 or 380x380x210mm for R models
Shipping weight (approx.)	: 12 kg   22 kg for R models (with batteries)
Fiber Optic Distribution Frame (ODF)	: mounted with 4 FC adapters, pigtails, patch cords
Heater with thermostats (for H models)	: NSBon-18 option, Fan Heater
Uninterruptible Power Supply (for R models)	: NR-48VDC-360VA with mounting kit for batteries 7Ah x4
<b>Hardware specification</b>	<b>Managed Industrial switch NIS-3500-3204PGE</b>
4x 10/100/1000Base-T RJ45 802.3bt PoE	IEEE 802.3af / 802.3at / 802.3bt (PD Alive Check)
1x 10/100/1000Base-T RJ45	802.3bt PoE 90W   UPoE 95W   802.3at 36W   Force 60W
2x 100/1000M SFP slots (with DDM)	G.8032 ERPSv2 Ring protection; 2 DI   2 DO
<b>Management Interface   Diagnostic</b>	
Console/CLI, Web GUI, Telnet, SNMP   Syslog, VLAN mirroring, RMON, SNMP Trap	
<b>Network Protocols :</b>	
<b>Spanning Tree:</b> STP, RSTP, MSTP; <b>Ring Topology:</b> G.8032 ERPSv2, Chain; <b>VLAN:</b> Port-based, 802.1q tag-based, 802.1ad Q in Q; <b>IGMP</b> Snooping v1/v2/v3 & Querier; <b>QoS:</b> 802.1p, 8 queues per port, WRR/SPQ; <b>DHCP</b> Client, Server, Relay, Snooping, Option 82; 802.1ab <b>LLDP</b> ; Multicast/Broadcast/Flooding <b>Storm Control</b> ; Access Control: IP/ MAC-based/ 802.1x authentication; <b>Security:</b> HTTPs, SSH, Radius Client; NTP/SNTP;	

