
Profile

- Analog position indicator
- Measured value acquisition based on the gravity principle
- High stability thanks to doubly supported pointer shaft
- Very robust, glass-fiber reinforced plastic housing
- Wide range of gear ratios
- Special scales, also for small numbers of pieces
- Dustproof, oil-filled or waterproof versions





Mechanical data

Feature	Technical data	Additional information
Housing	reinforced plastic	
Weight	0.1 kg	N, W design
	0.1 kg	P design



Order

Ordering information

One or more system components are required:

Handwheel HR... www.siko-global.com
Handwheel HS... www.siko-global.com
Handwheel HS... www.siko-global.com
Handwheel HS... www.siko-global.com
Handwheel HG... www.siko-global.com
Handwheel KHB... www.siko-global.com

Ordering table

Feature	Ordering data	Specification	Additional information
Version	N	dust-proof	
	P	oil-filled	
	W	waterproof	
Gear ratio	B	1, 2, 3, 6, 10, 12, 15, 18, 20, 24, 30, 36, 48, 50, 60, 72, 84, 96, 100	
		others on request	
Sense of rotation	i	clockwise ascending values	
	e	counter-clockwise ascending values	
Pointer	1	red with transmission	
	2	red with transmission + black 1:1	
Covering glass	S	plastic	
	Α	synthetic material, aceton-resistant	
Scale	N	normal scale	related to the transformation ratio
	VK	special scale	customer-specific, no VK for first production
Multi-color scale	C1	1-colored	
	C2	2-colored	
	C3	3-colored	

Order key



Scope of delivery: S50/1