







Safety quarter turn with mask

PROGRAM 1000

Beschlagteile



with stainless steel version



Insert square or triangular



Insert double bit

Press down insert turn quarter turn!

Housing and insert material on choice, mask zinc die raw, screw and earthnut m.s. zinc plated and/or screw and nut stainless steel, with spring and seal

	zinc die chrome pl.	AISI 316
Square female 6mm	on request	on request
Square female 7mm	1000-U818-02IA	on request
Square female 8mm	1000-U818-03IA	on request
Square female 8mm slotted	on request	on request
Triangular 6,5 CNOMO	on request	on request
Triangular 7	1000-U818-04IA	on request
Triangular 8	1000-U818-05IA	on request
Triangular 9	on request	on request
Triangular 10	on request	on request

Housing and insert material on choice, mask zinc die raw, screw and earthnut m.s. zinc plated and/or screw and nut stainless steel, with spring and seal

	zinc die chrome pl.	AISI 316
Double bit 3 mm RH version	1000-U819-01IA	on request
Double bit 3 mm LH version	1000-U819-03IA	on request
Double bit 5 mm RH version	1000-U819-02IA	on request
Double bit 5 mm LH version	1000-U819-04IA	on request

Safety quarter turn:
This lock is of a vibration proof design. Depending on the installation location and operational conditions, specific checks are necessary and/or supplementary measures of fastening required.

Version double bit: Key only removable in locked position

Keyhole for double bit according to key DIN 43668.

Note:
The H-dimension will be reduced by 2 mm when used with finger pull (see page 1C-320)

Further parts see page
 – Cam without catch 1C-120
 – Accessories 1C-320
 up to 1C-380
 – Key 12B-120