



A Fluke Company

# Food Tracker<sup>®</sup>

## Data Loggers



<b>DP2162A</b>	Type T thermocouple	6 channels
<b>DP2166A</b>	Type K thermocouple	6 channels
<b>DP2182A</b>	Type T thermocouple Humidity option 1 channel / RF telemetry option	8 channels
<b>DP2186A</b>	Type K thermocouple Humidity option 1 channel / RF telemetry option	8 channels
<b>Accuracy</b>	$\pm 0.2^{\circ}\text{C}$ ( $\pm 0.4^{\circ}\text{F}$ )	
<b>Resolution</b>	$\pm 0.1^{\circ}\text{C}$ ( $\pm 0.2^{\circ}\text{F}$ )	
<b>Thermocouple Type</b>	T and K	
<b>Measurement Range</b>	Type K -150°C to 1370°C (-238°F to 2498°F) Type T -196°C to 400°C (-320°F to 752°F)	
<b>Operating Temperature</b>	-40°C to 85°C (-40°F to 185°F) <i>without thermal barrier</i>	
<b>Humidity Option</b>	Available on 8 channel system	
<b>Real-time Monitoring</b>	8 channel system: Hardwired (via comms cable) Standard/RF telemetry option (TM21)	
	6 channel system: Hardwired (via comms cable) standard	
<b>Protection</b>	IP67 (submersion in water at 1 m (3.2 ft) depth for 30 minutes) <i>without thermal barrier</i>	
<b>Sample Interval</b>	0.5 seconds to 50 minutes (standard use—temperature only) 2.0 seconds to 50 minutes (radio telemetry—temperature only) 2.0 seconds to 50 minutes (temperature and humidity measurement)	
<b>Memory</b>	1.81 MB 16 hours data collection (8 thermocouples / 0.5 second sampling)	

# TECHNICAL SPECIFICATIONS

<b>Communications</b>	Serial or USB computer interface
<b>CI1025</b>	Serial cable (RS232)
<b>CI1026</b>	USB cable

## Communication socket cap

Datalogger communications port cap providing protection from dirt and water/salt damage.

## Thermocouple plug shroud

Used for mounting thermocouples for repeat runs, so they can be plugged into the logger in one action, guaranteeing the correct thermocouple is plugged into the correct channel position on the logger.

<b>CI131</b>	8 channel plug shroud
--------------	-----------------------

## Channel blanking plug

**DPI213A**-Inserted into any channel not fitted with a thermocouple to provide protection to the connector from dirt, etc. and waterproofing

## Operation

Multiple Runs (up to 8 individual repeat runs before download)

## Data collection start

Start/Stop button, temperature rise/fall, date and time

## Battery

Rechargeable NiMH (recharge time 2.5 hours)

## Battery Life (full charge)

Temperature, only (0.5 second sample interval) = 120 hours

Temperature, only (10 minutes sample interval) = 250 hours

Telemetry (2.0 second sample interval) = 65 hours


Humidity (2.0 second sample interval) = 120 hours

<b>CH0070</b>	Battery Charger (International)
---------------	---------------------------------

Supplied with pin configuration to suit region



Thermocouple Plug Shroud



Channel Blanking Plugs

## The Worldwide Leader in Temperature Profiling



**Europe and Asia**  
DATAPAQ Limited  
Lothbury House, Cambridge Technopark  
Newmarket Road  
Cambridge CB5 8PB, UK  
Tel: +44 1223 652 400  
Fax: +44 1223 652 401  
E-mail: sales@datapaq.co.uk

**North and South America**  
DATAPAQ Inc.  
3 Corporate Dr. Unit 1  
Derry, NH 03038, USA  
Tel: +1 603 537 2680  
Fax: +1 603 537 2685  
E-mail: sales@datapaq.com

**France** Tel: 0800 901 666  
Fax: +44 1223 652 401  
E-mail: vente@datapaq.co.uk  
**Germany** Tel: +49 5733 9107 0  
Fax: +49 5733 9107 27  
E-mail: sales@datapaq.de  
**Italy** Tel: +39 335 284 029  
Fax: +44 1223 652 401  
E-mail: vendite@datapaq.co.uk

