

Data Sheet

Perforated Metal Plank Type BR

The perforated metal plank type BR "Raute" is particularly suitable for areas of heavy loads on small contact areas due to its rhomb profile with extra high punching (punched holes 2.5 mm). Here, for example, vehicle navigability on ramps or parking areas are to be considered.

Technical Details

Material	Steel S235JR: Stainless Steel: Aluminium:	1,5 mm, 2,0 mm, 2,5 mm, 3,0 mm 2,0 mm, 2,0 mm, 2,5 mm
Surface treatment	Steel: Stainless Steel: Aluminium:	untreated, hot-dip galvanized, pre-galvanized untreated, pickled untreated, pickled, anodized
Free cross section	Width: 150 mm: 200 mm: 250 mm: 300 mm:	~ 23,0 % ~ 33,6 % ~ 36,2 % ~ 42,5 %
Width	150 mm, 200 mm, 250 mm, 300 mm (other widths possible in demand)	
Height	30 mm, 50 mm, 75 mm, 100mm, 150 mm Corresponding to width and statical specification)	
Ball proof	Ø 35 mm – the Ø 35 mm ball don't fall through	
Slip resistance	R11 / V10 (Steel hot-dip galvanized)	
Longitudinal grid	125 mm (62,5 mm)	
Production length	max. 10 m, depending transport limited	

