

# AIRPURION 36



The UV-plant AIRPURION 36 with an irradiation width of 750 mm consists of a matt anodized aluminium profile with matching cover sheets.

The radiator's compartment is designed for housing a pristine-polished aluminium reflector. On its rear side the cabling as well as the electronic cut-in unit is integrated into the housing.

applications	product line	AIRPURION 36
pharmacy	irradiation width	750 mm
medical technology	disinfection 80%	approx. 53 m <sup>3</sup>
	disinfection 88%	approx. 26 m <sup>3</sup>
laboratories	weight	3,0 kg
ripening rooms	life time of lamps	10.000 h
	dimension (L x B x H in mm)	1000 x 67 x 100
	number of lamps	1
	protection grade	IP 54
	electrical connection	110-240 50/60 Hz
	total power	36 W
	over current protection	10 A
<b>advantages</b>		
suitable for direct or indirect irradiation		
not affecting smell or taste		
low-maintenance operation		
low operational costs		

## alternating current (VAC)

article number: 160 01100 0000

alternating current AC	•
wide voltage	•
splinter protection	•
dry room	•
humid room	•

article number: 160 01200 0000

article number: 160 04000 0000

alternating current AC	•
wide voltage	•
splinter protection	•
dry room	•
humid room	•

## equipment AIRPURION 36

AIRPURION wire suspension  
article number: 160 00011 0000



AIRPURION mounting rack  
article number: 160 00040 0000

PURION UV-lamp 36 W  
article number: 200 00400 0000



service-kit  
article number: 292 00900 0000

