



# TransiTec

ANLAGENBAU GMBH



## Pneumatic conveyor Series S-WS



### Pneumatic conveyor TransiTec

- For the conveying of granulate and dry powder products
- Large filtration surface
- Cleaning of the filter by air pressure  
Cleaning of the filter by adjustable clearance
- High throughput
- Ideal for the conveying over long distances
- Application area: food and plastics industry  
as well as in the sector of chemistry and environment.



Différent  
filter sizes



Electrical control cabinet  
with integrated freely  
programmable steering  
- setting of the suction time  
- calibration of the filter cleaning.



Electrical control box and side channel  
blower mounted on welded frame  
- the frame is optionally mounted  
on guide rolls with positioners.

Various filter sizes with suitable  
face up to 10 m<sup>2</sup>.



Removable top for filter cleanse  
- with clamps for vacuum-tight closing.

One big product outlet nozzle  
ensures a free and quick  
emptying of the product  
precipitation hopper.



Automatic filter cleaning after each  
suction operation by means of  
intermittent cleaning with compressed  
air. A big compressed air storage vessel  
ensures the adequate  
impulse intensity.



The design of the pneumatic conveyor depends of the product which has to be conveyed., the conveying distance and the required throughput. The design occurs depending of the volume of the product precipitation hopper and depending of the throughput of the side channel blower.



TransiTec Anlagenbau GmbH  
Hanns Martin Schleyer Straße 29 - D-47877 Willich  
Tel. +49 (0) 2154 / 9416-30 - Fax : +49 (0) 2154 / 9416-59  
Email : info@transitec.de - www.transitec.de