

➤ Our technology. Your success.

Pumps • Valves • Service



SISTO-C Diaphragm valves for sterile applications



Applications:

Hygienic and sterile handling of fluids in the food, beverage and pharmaceutical industries

Further infomation:

www.ksb.com/products

Your contact:



SISTO-CM511



SISTO-CM501



SISTO-CT



SISTO-C Diaphragm valves for sterile applications



Maximum service life and pressure limit (PN16)
thanks to enclosed and spiral-supported diaphragm;
operating pressure up to 20bar

Simplified installation and control of the drain angle

Self-drained; drain angle indicated by laser marking

Optimum conditions for fluid purity
due to valve hydraulics without dead volume

High energy efficiency

Lower pressure losses thanks to optimized flow profile

Excellent functional reliability

The floating diaphragm suspension prevents
damages of the diaphragm

Reliable Operation

The stem and all internal operating elements
are not in contact with the fluid

**Reliable sealing to atmosphere and
absolutely tight shut-off**

The diaphragm provides hermetic sealing

Materials

Body	1.4435 ; 1.4539 and different Hastelloy qualities
Bonnet	1.4409
Diaphragm	EPDM, TFM-bonded, TFM/EPDM 2-pieces

SISTO-C Kvs value			DIN 11866 series A	DIN 11866 series B	DIN 11866 series C
DN	NPS	MD	Kvs-value m³/h	Kvs-value m³/h	Kvs-value m³/h
6	1/4"	30	1,1	1,5	0,6
8	5/16"	30	1,8	2,2	-
10	3/8"	30	2,1	-	1,7
15	1/2"	30	-	-	2,1
10	3/8"	40	-	4,5	-
15	1/2"	40	5	5,2	2,6
20	3/4"	40	-	-	4,9
20	3/4"	65	11,8	14,7	-
25	1"	65	16,5	17,5	13,8
32	1 1/4"	92	34	43	-
40	1 1/2"	92	42,5	45,5	39
50	2"	115	65	69	62
65	2 1/2"	115	-	-	71
65	2 1/2"	168	137	149	-
80	3"	168	156	161	151
100	4"	202	245	255	237



SISTO Armaturen S. A. • 18, rue Martin Maas • 6468 Echternach / Luxembourg
Tel. +352 325085-1 • Fax +352 328956 • Email: sisto@ksb.com . www.sisto.lu

A KSB Company •