


## Manual Blasting Machines

### CO2 Snow Blasting Machine SJ-25

- For large surfaces and stubborn contaminations
- Powerful round nozzles
- Flat nozzles with blasting widths of up to 100 mm (4")
- Available as Desktop and Trolley
- No power supply, as driven pneumatically



Storage space for nozzles and tools



Removable control handle



Safe supply connections



Clear-cut control panel

#### Technical Data

Dimensions Desktop - length x width x height	580 mm x 360 mm x 475 mm (22.8" x 14.2" x 18.7")
Weight Desktop	25.6 kg (56.4 lb)
Dimensions Trolley - length x width x height	620 mm x 490 mm x 1050 mm (24.4" x 19.3" x 41.3")
Weight Trolley	33.2 kg (73.2 lb)
Compressed air consumption	1 to 6 m <sup>3</sup> /min (35 bis 212 scf/min)
Compressed air operating pressure	5 to 16 bar (72 bis 232 psi)
Compressed air connection	DIN3489, customer-specific
Compressed air quality	dry, oil and particle free
Liquid CO2 consumption	0.4 to 1.5 kg/min (0.9 to 3.3 lb/min)
Liquid CO2 operating pressure	20 to 100 bar (290 to 1,450 psi)
Liquid CO2 connection	customer-specific
Blasting pressure	2 to 16 bar (29 to 232 psi)
Sound power level	80 to 120 dB(A)