


RIVDOM® eBZ 3

Battery-powered setting tool for blind rivets



The **HONSEL Rivdom eBZ 3** battery riveter was developed specially for the demands of the setting of high-strength blind rivets with 6.4 and 7.8 mm diameter with grooved rivet stud!

up to
7.8 mm

The clamping jaws specially designed for this geometry and a modified clamping mechanism **guarantee reliable and positive settings** of FERRO® BULB high-strength blind rivets (or comparable products) with a stud diameter from 3.8 to 6.15 mm. This also helps to minimise wear on the clamping jaws.

Rivdom eBZ 3



24,000 N!
MAXIMUM POWER
with cordless riveting



High-strength FERRO® BULB blind rivets with 7.8 mm diameter in use, for example, in truck production.



The **HONSEL RIVDOM eBZ 3** is supplied as standard with retainer nosepieces.

Wear parts can be changed practically without the use of tools.

Family facts on the **HONSEL** battery riveters on ► page <AE>.



2.4	3.0	3.2	4.0	4.8	5.0	6.0	6.4	8.0
							Aluminium	
							Steel	
							Stainless steel	
							Copper	

max. 6.1 mm

2.1 kg
(incl. 2.0 Ah battery)

30 mm

24,000 N

< 30 min.

- 1x Rivdom eBZ 3 battery riveter with brushless motor in **HONSEL L-Boxx®**
- 20V/2.0 Ah Li ion battery with optical state-of-charge indicator (number depending on variant)
- 1x Rivdom-PLUS quick-charger
- 2x retainer nosepieces in box
- 1x stud collector "L"
- 1x each belt clip, hanger bracket and cover cap

Art.-Nr. **32052800000-010-1** (1x Akku 20V/2Ah)

Art.-Nr. **32052800000-020-1** (2x Akku 20V/2Ah)

