



## SPRING WASHER VHD - SN60727 (Stainless Steel Version)

| Size         | d1    | Tol. | d2 max. | h min. | b    | Tol. | s    | Tol. | kg/1000 pcs. |
|--------------|-------|------|---------|--------|------|------|------|------|--------------|
| <b>M 2,5</b> | 2,60  | +0,3 | 5,10    | 1,00   | 0,90 | +0,2 | 0,50 | +0,2 | 0,05         |
| <b>M 3</b>   | 3,10  |      | 6,20    | 1,30   | 1,20 |      | 0,70 |      | 0,11         |
| <b>M 4</b>   | 4,10  |      | 7,60    | 1,40   | 1,40 |      | 0,80 |      | 0,15         |
| <b>M 5</b>   | 5,10  |      | 9,20    | 1,80   | 1,70 |      | 1,10 |      | 0,36         |
| <b>M 6</b>   | 6,10  | +0,4 | 11,80   | 2,40   | 2,35 | +0,3 | 1,50 | +0,3 | 0,83         |
| <b>M 8</b>   | 8,10  |      | 14,80   | 3,00   | 2,85 |      | 1,90 |      | 1,60         |
| <b>M 10</b>  | 10,10 | +0,5 | 18,00   | 3,40   | 3,30 | +0,4 | 2,05 | +0,3 | 2,50         |
| <b>M 12</b>  | 12,10 |      | 21,00   | 3,90   | 3,80 |      | 2,35 |      | 3,80         |
| <b>M 14</b>  | 14,10 |      | 24,00   | 4,70   | 4,30 |      | 2,85 |      | 6,00         |
| <b>M 16</b>  | 16,20 | +0,8 | 27,30   | 5,50   | 4,80 | +0,4 | 3,30 | +0,4 | 8,90         |
| <b>M 18</b>  | 18,20 |      | 29,40   | 5,50   | 4,80 |      | 3,30 |      | 9,70         |
| <b>M 20</b>  | 20,20 | +1,0 | 33,60   | 6,30   | 5,80 | +0,5 | 3,80 | +0,4 | 15,20        |
| <b>M 24</b>  | 24,50 |      | 40,00   | 6,30   | 6,75 |      | 4,80 |      | 26,20        |

Available material versions: 1.4310 (A2) / 1.4401 (A4)

Technical standard: DIN 128A