



PREINSULATED 45° ELBOW IN ACCORDANCE WITH TS EN 448 STANDARDS

| INNER PIPE | NOMINAL DIAMETER | DN | Ø25 | Ø32 | Ø40 | Ø50 | Ø65 | Ø80 | Ø100 | Ø125 | Ø150 | Ø200 | Ø250 | Ø300 | Ø350 | Ø400 | Ø450 | Ø500 | Ø600 | Ø700 | Ø800 | Ø900 | Ø1000 | Ø1100 | Ø1200 |
|-------------|--------------------|------|------|------|------|------|------|------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|---------|---------|---------|
| | | inch | 1" | 1 ¼" | 1 ½" | 2" | 2 ½" | 3" | 4" | 5" | 6" | 8" | 10" | 12" | 14" | 16" | 18" | 20" | 24" | 28" | 32" | 36" | 40" | 44" | 48" |
| | OUTER DIAMETER (d) | mm | 33,7 | 42,4 | 48,3 | 60,3 | 76,1 | 88,9 | 114,3 | 139,7 | 168,3 | 219,1 | 273,0 | 323,9 | 355,6 | 406,4 | 572,2 | 508,0 | 610,0 | 711,1 | 813,0 | 914,0 | 1.016,0 | 1.118,0 | 1.219,0 |
| CASING PIPE | OUTER DIAMETER(D) | mm | 90 | 110 | 110 | 125 | 140 | 160 | 200 | 225 | 250 | 315 | 400 | 450 | 500 | 560 | 630 | 710 | 800 | 900 | 1000 | 1200 | 1200 | 1400 | 1400 |
| L LENGTH | | | 1000 | 1000 | 1000 | 1000 | 1000 | 1000 | 1000 | 1000 | 1000 | 1000 | 1000 | 1000 | 1200 | 1500 | 1500 | 1500 | 1800 | 1800 | 1800 | 1800 | 2000 | 2000 | 2000 |